

PRODUCT-DETAILS

OT100F3C

OT100F3C CHANGE-OVER SWITCH



General Information

Extended Product Type	OT100F3C
Product ID	1SCA105008R1001
EAN	6417019391397
Catalog Description	OT100F3C CHANGE-OVER SWITCH
Long Description	OT100F3C CHANGE-OVER SWITCH, Handle and shaft need to be ordered separately, Open transition

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303008M0203

Dimensions

Product Net Width	140 mm
-------------------	--------

Product Net Height	100 mm
Product Net Depth / Length	86 mm
Product Net Weight	0.9 kg 140 lb

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 100 A (500 V) 100 A (690 V) 100 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 100 A (500 V) 100 A (690 V) 100 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 80 A (500 V) 60 A (690 V) 40 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 37 kW (500 V) 37 kW (690 V) 37 kW
Conventional Free-air Thermal Current (I_{th})	$\vartheta = 40^\circ\text{C}$ 115 A
Conventional Thermal Current (I_{the})	Fully Enclosed 115 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	750 V
Rated Operational Voltage	750 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 2.5 kiloampere rms
Power Loss	4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	10 ... 70 mm ²
Degree of Protection	Front IP20
Mechanical Durability	6000 cycle
Transition Type	Open

Technical UL/CSA

Horsepower Rating UL/CSA	(acc. to UL 200 V) 30 Hp (acc. to UL 208 V) 30 Hp (acc. to UL 240 V) 30 Hp (acc. to UL 480 V) 50 Hp (acc. to UL 600 V) 50 Hp
Ampere Rating UL/CSA	100 A

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303021D0201
Instructions and Manuals	1SCC303008M0203
RoHS Information	1SCC301183D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	102 mm
Package Level 1 Depth / Length	205 mm
Package Level 1 Height	103 mm
Package Level 1 Gross Weight	0.9 kg
Package Level 1 EAN	6417019391397

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601402
E-Number (Sweden)	3171265

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

