



Odace - RJ45 data connector cover - 1 socket - white - with plastic fixing frame

S520400

Main

Range of product	Odace	
Product or component type	Central plate	
Device presentation	Cover plate with plastic fixing frame	
Type of packing	Paint cover	
Quantity per set	Set of 5	

Complementary	
Wiring device mounting	Flush
Product destination	RJ45 connector
Fixing mode	By claw kit By screws
Colour tint	White (RAL 9003)
Surface finish	Glossy
Product compatibility	Infraplus Actassi s-one
Socket number	1
Shape of screw head	Pozidriv No 1
Material	Thermoplastic ABS-UV stabilised: centre plate PBT (polybutylene terephthalate) GF30: support frame
Height	71 mm
Width	71 mm
Depth	34.2 mm
Embedding depth	18.2 mm
Net weight	0.027 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

		ro			

Ambient air temperature for storage	-550 °C
Ambient air temperature for operation	545 °C
IK degree of protection	IK04

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	30 g
Package 1 Height	3.5 cm
Package 1 width	7.1 cm
Package 1 Length	7.2 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Weight	237 g
Package 2 Height	5.8 cm
Package 2 width	9 cm
Package 2 Length	37 cm
Unit Type of Package 3	S02
Number of Units in Package 3	30
Package 3 Weight	1.721 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm
·	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty 18 mon	
-----------------	--