



### Main

Range of product	Odace
Aesthetic name	Styl
Product or component type	Socket-outlet
Device presentation	Complete socket-outlet
Socket number	2
Type of packing	Paint cover
Quantity per set	Set of 10
Number of terminals	3

### Complementary

Device mounting	Flush
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	German
Fixing mode	By screws
Colour tint	White (RAL 9003)
Surface finish	Glossy
Rated current	16 A at 250 V AC 50 Hz
Service life in cycles	5000 cycles
Electrical durability	5000 cycles
Connections - terminals	Screw terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	1 x 1.5...2 x 4 mm <sup>2</sup> for rigid cable(s) 1 x 1.5...2 x 4 mm <sup>2</sup> for stranded cable(s) 1 x 1.5...2 x 4 mm <sup>2</sup> for flexible cable(s)
Wire stripping length	12 mm
Material	ASA + PC: mechanism cover

PC (polycarbonate) GF10 FR: casing  
Sheet metal: support frame

Height	126 mm
Width	85 mm
Depth	49 mm
Embedding depth	27.1 mm
Net weight	0.109 kg
Resistance to chemical agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane

## Environment

Ambient air temperature for storage	-5...50 °C
Dielectric strength	2000 V
Ambient air temperature for operation	5...35 °C
Standards	UNE 20315-1-2 UNE 20315-1-1
IK degree of protection	IK04
IP degree of protection	IP21D

## Packing Units

Package 1 Weight	0.116 kg
Package 1 Height	0.500 dm
Package 1 width	0.850 dm
Package 1 Length	1.260 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------