



Main

Range of product	Odace
Product or component type	Combined control device
Device presentation	Mechanism with plastic fixing frame
Switch additional information	Normally open or closed according to wiring
Switch application	Electrical circuit control
Type of packing	Paint cover
Quantity per set	Set of 5
Sale per indivisible quantity	1

Complementary

Wiring device mounting	Flush
Switch function	2-way switch + NO pushbutton
Number of rocker	2
Actuator	Rocker and pushbutton
Fixing mode	By screws
Colour tint	White (RAL 9003)
Surface finish	Glossy
Rated current	10 AX - 250 V AC 50/60 Hz
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un with $\cos \varphi = 0.3$
Service life in cycles	20000 cycles @ ON and OFF at rated voltage with $\cos \varphi = 0.6$
Number of terminals	6 screwless terminals
Shape of screw head	Pozidriv No 1
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² stranded cable(s) 1 x 1.5...2 x 2.5 mm ² flexible cable(s) 1 x 1.5...2 x 2.5 mm ² rigid cable(s)
Wire stripping length	12 mm
Local signalling	Lightable
Material	Casing : PC (polycarbonate) GF10 FR Support frame : PBT (polybutylene terephthalate) GF30 Centre plate : thermoplastic ABS-UV stabilised
Height	71 mm
Width	71 mm
Depth	33.6 mm
Embedding depth	18.75 mm
Product weight	0.04 kg

Environment

Ambient air temperature for storage	-5...50 °C
Dielectric strength	0...2000 V
Ambient air temperature for operation	5...35 °C
Standards	2006/95/EEC EN 60669-1
Product certifications	NF N LCIE : NF 619318A Aenor : 030/2237
IK degree of protection	IK04
IP degree of protection	IP21 D
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1101 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations