



Main

Range of product	Odace
Product or component type	Data socket
Device presentation	Mechanism with plastic fixing frame
Data socket type	RJ45 8 contact(s) Cat.6 <= 250 MHz
Type of packing	Paint cover
Quantity per set	10 pieces
Sale per indivisible quantity	1
Product certifications	EC verified as per VDIB177x6Uyy for connector

Complementary

Wiring device mounting	Flush
Socket number	2
Organization of wire	Unshielded twisted pair
Cable shielding type	UTP
Product compatibility	Infraplus Actassi s-one
Fixing mode	By screws
Colour tint	Aluminium
Connections - terminals	IDC
Number of loop terminals	1
Material	PBT (polybutylene terephthalate) GF30 support frame Thermoplastic ABS-UV stabilised centre plate
Height	71 mm
Width	71 mm
Depth	41.7 mm
Embedding depth	25.7 mm
Product weight	0.05 kg

Environment

Ambient air temperature for storage	-5...50 °C
Ambient air temperature for operation	5...35 °C
Standards	EN 50173-1 ISO/IEC 11801 IEC 60603-7 TIA/EIA-568 IEC 60603-7-5 ANSI/TIA/EIA-568-B-2 ANSI/TIA/EIA-568-B-2-1
IP degree of protection	IP21
IK degree of protection	IK04
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free